

**Männäntiivisteet  
2-toimiset  
A-W**

|  |   |
|--|---|
|  | <p><b>Toleranssit:</b><br/> <math>\varnothing D: &lt; 120</math> H11 <math>\varnothing d: &lt; 120</math> js11 H: +0,10/+0,35<br/> <math>\varnothing D: &gt; 120</math> H10 <math>\varnothing d: &gt; 120</math> js10 H: +0,10/+0,35</p> <p><b>Materiaalit:</b><br/>         NBR / Kudosvahvisteinen kumi / Asetaalimuovi</p> <p><b>Käyttöolosuhteet:</b><br/>         Paine : &lt; 700 bar<br/>         Lämpötila: -40 °C ... +110 °C<br/>         Nopeus : &lt; 0,5 m/s</p> |
|--|---|

| <u>Nimike</u> | <u>d</u> | <u>D</u> | <u>H</u> | <u>1 kpl</u> | <u>100 kpl</u> |
|---------------|----------|----------|----------|--------------|----------------|
| A80/60X35W    | 80,00    | 60,00    | 35,00    | 96,10        | 80,08          |
| A100/80X35W   | 100,00   | 80,00    | 35,00    | 118,31       | 98,59          |
| A125/100X45W  | 125,00   | 100,00   | 45,00    | 181,49       | 151,24         |
| A130/105X45W  | 130,00   | 105,00   | 45,00    | 192,34       | 160,28         |
| A140/115X45W  | 140,00   | 115,00   | 45,00    | 182,07       | 151,72         |
| A150/125X45W  | 150,00   | 125,00   | 45,00    | 204,27       | 170,23         |
| A160/135X45W  | 160,00   | 135,00   | 45,00    | 215,45       | 179,54         |
| A170/140X45W  | 170,00   | 140,00   | 45,00    | 264,98       | 220,81         |
| A180/155X45W  | 180,00   | 155,00   | 45,00    | 264,98       | 220,82         |
| A190/165X45W  | 190,00   | 165,00   | 45,00    | 291,18       | 242,65         |
| A200/175X45W  | 200,00   | 175,00   | 45,00    | 291,18       | 242,65         |
| A220/195X45W  | 220,00   | 195,00   | 45,00    | 321,51       | 267,92         |
| A250/225X45W  | 250,00   | 225,00   | 45,00    | 361,02       | 300,85         |
| A280/255X45W  | 280,00   | 255,00   | 45,00    | 424,41       | 353,67         |
| A300/275X45W  | 300,00   | 275,00   | 45,00    | 430,92       | 359,10         |